

Kroflex 840

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 23-26
- **Thickness (mm)** NS
- **Wrist** Knitted wrist
- **Colour/Color** Blue
- **Interior finish** Seamless textile support from superior strength fibres
- **Exterior finish** Embossed texture
- **Size / EAN** 7 8 9 10
- **Packaging** 1 pair/bag - 12 pairs/box - 72 pairs/carton



PERFORMANCE RESULTS

Certification category 2



X2XXXX



3543
ISO 13997 :
20.4 N (2080 g)

ISO 13997 defines the weight on the blade required to cut in a single movement.

Data was obtained according to ISO 13997, from the average of several measurements. As individual specimens will obviously have greater or lesser cut resistance than the average, so this result can provide only a general indication of the cut resistance of any protective material.

Legends



MECHANICAL HAZARDS
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Puncture resistance
 └─ Tear resistance
 └─ Blade cut resistance
 └─ Abrasion resistance



LOW CHEMICAL PROTECTION
EN 374



MICRO-ORGANISMS
EN 374



RADIOACTIVE CONTAMINATION
EN 421



SPECIFIC CHEMICAL PROTECTION
EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Water permeability
 └─ Contact cold resistance
 └─ Convective cold resistance



HEAT AND FIRE
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Resistance to large quantities of molten metal
 └─ Resistance to small drops of molten metal
 └─ Radiant heat resistant
 └─ Convective heat resistance
 └─ Contact heat resistance
 └─ Burning behaviour

For more details: www.mapa-pro.com

Kroflex 840

DESCRIPTION AND GENERAL PROPERTIES

- Highest protection level against cuts
- Good thermal insulation of the hand
- Good grip for picking up parts safely, due to embossed texture
- Good puncture-resistance

MAIN FIELDS OF USE

Ceramic and plastics industry

- Post-injection handling of hot plastic parts
- Handling of composite materials after heat processing

Glass industry

- Handling glass sheets

Construction Industry (Carpenters/Joiners)

- Cutting wood
- Installing steel structures
- Assembly
- Screwing
- Studwork

Local Authorities (Waste Collection and Processing)

- Processing waste at a sorting center

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.
- Inspect the gloves for cracks or snags before reusing them.
- It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves, nor to use them next to moving machinery.

Storage conditions

Store the glove in their original packaging protected from heat, light and humidity.

Laundering conditions

Caution: improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/12/08/0473

- Issued by the notified body nr

0075

C.T.C. – rue H. FRENKEL - F-69367 LYON CEDEX 07