

# Titan 385

## DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (cm) 24-26
- Thickness (mm) 1.40
- Wrist Safety cuff
- Colour/Color Blue
- Interior finish Textile support
- Exterior finish Ventilated back
- Size / EAN 8 9 10
- Packaging 10 pairs/bag - 100 pairs/carton



## PERFORMANCE RESULTS

### Certification category 2



4111

### Legends



**MECHANICAL HAZARDS**  
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4  
 └─ Abrasion resistance  
 └─ Blade cut resistance  
 └─ Tear resistance  
 └─ Puncture resistance



**LOW CHEMICAL PROTECTION**  
EN 374



**MICRO-ORGANISMS**  
EN 374



**RADIOACTIVE CONTAMINATION**  
EN 421



**HEAT AND FIRE**  
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4  
 └─ Burning behaviour  
 └─ Contact heat resistance  
 └─ Convective heat resistance  
 └─ Radiant heat resistant  
 └─ Resistance to small drops of molten metal  
 └─ Resistance to large quantities of molten metal



**SPECIFIC CHEMICAL PROTECTION**  
EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS**  
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1  
 └─ Convective cold resistance  
 └─ Contact cold resistance  
 └─ Water permeability

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

## DESCRIPTION AND GENERAL PROPERTIES

- Freedom of movement: exceptionally comfortable textile support (no seams on the working surfaces)
- Excellent resistance to oils and greases
- Longer service life: quality of textile support and nitrile coating

## MAIN FIELDS OF USE

### Other industries

- Household waste collection
- Forestry

### Mechanical industry

- Metal shearing or cutting
- Handling of thick, untrimmed sheet metal (not sharp-edged)

### Local Authorities (Waste Collection and Processing)

- Waste collection

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the « CE »-type-tests.
- It is not recommended for persons sensitized to dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Rub over the gloves stained with oil or grease before taking them off.

### Storage conditions

Store the gloves in their original packaging protected from light and humidity.

### Laundering conditions

Caution : using the gloves or submitting them to cleaning or laundering process which is not specifically recommended can alter their performance levels.

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

## LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate  
0075/014/162/05/03/0061
- Issued by the notified body nr  
0075  
C.T.C – F-69367 LYON CEDEX 07